



d ₁		Toleranz / tolerance	Fügespiel / clearance max
from / to			mm
18	30	H6 / J6	0,017
30	50	H6 / h6	0,032
50	80	H6 / g6	0,048

Bestellbeispiel / Ordering Example WSR 280 - 50 x 90
Typ / Type d x D

Hohlwelle / Hollow Shaft	Welle / Shaft	Außen / Outer	Drehmoment / Torque	Abmessungen / Dimensions (mm)			Spannschraube / Locking Screw	
ød (mm)	ød ₁ (mm)	øD (mm)	TKN	L1	L2	L3	S	TA
	19		160					
24	20	50	230	22	18	15	M6	12
	22		290					
	24		370					
30	25	60	425	24	20	17	M6	12
	26		475					
	27		470					
36	30	72	655	27,5	22	19	M8	30
	33		855					
	27		480					
38	30	72	645	27,5	22	19	M8	30
	33		855					
	34		805					
40	35	80	885	29,5	24	20,5	M8	30
	37		960					
	35		810					
44	36	80	880	39,5	24	20,5	M8	30
	37		970					
	38		1140					
50	40	90	1310	31,5	26	22	M8	30
	42		1530					
	42		1300					
55	45	100	1600	34,5	29	24,5	M8	30
	48		1950					
	48		1710					
62	50	110	1950	34,5	29	24,5	M8	30
	52		2150					
	50		1900					
68	55	115	2510	35	29,5	24,5	M8	30
	60		3140					
	55		2750					
75	60	138	3400	38	31	25	M10	60
	65		4050					
	60		3300					
80	65	141	4150	38	31	25	M10	60
	70		4940					
	65		5550					
90	70	155	6650	45	38	31,5	M10	60
	75		7950					
	70		10550					
100	75	170	11750	50,5	43,5	36,5	M10	60
	80		13700					
	80		10450					
110	85	185	11830	57	49	40,5	M12	100
	90		13710					
	90		14550					
125	95	215	16700	61,5	53,5	45	M12	100
	100		18800					